

APPLYING VINYL STICKERS

Please read all instructions prior to starting.

Sticker adhesive is automotive paint and glass safe (use an automotive wax or Goo-Gone to remove all residue). Recommended to apply stickers at temperatures above 50°F.

1. Lightly smooth the application tape (wax-type paper or clear-type plastic) over the vinyl sticker with a plastic scraper or credit card. Once the application tape is fixed to the vinyl, carefully pull it off the backing paper, ensuring ALL the pieces of the vinyl sticker stay attached to the application tape. The vinyl sticker will now be attached to the application tape with the adhesive side out, as shown below:



2. Ensure intended mounting surface is clean and dry, recommend using a glass type cleaner. Position the application tape containing the vinyl sticker over the intended mounting surface. If you anticipate difficulty in positioning your sticker you can spray the surface with an application fluid (recommended for stickers over 24 inches). The application fluid will keep the vinyl adhesive from sticking to the surface for 45-90 seconds giving you more time to make positioning adjustments.



3. Once your sticker is in the proper position, apply pressure to the application tape and sticker. For larger stickers, a plastic scraper or credit card may be used to force out all the air bubbles that may be trapped between the vinyl and surface, as shown below:



4. Grab a corner of the application tape and gently pull it off the surface containing the sticker, ensuring ALL pieces of the sticker stay attached to the surface. Apply pressure to the sticker. You're Done...



COURTESY OF:
MAY PRINTING
MayPrinting.com
Buffalo, New York

